

BX RANGE



IndigoVision



# Fisheye Camera

Amazing Megapixel video that delivers detail from every angle

Part of IndigoVision's professional BX Range, the Fisheye Camera delivers 360° visibility with pin-sharp detail. When used as part of IndigoVision's end-to-end system, any single point of failure is removed through IndigoVision's Distributed Network Architecture (DNA) technology.

## Key Features

SENSOR

- 6MP
- 12MP
- Day/Night
- WDR

COMPRESSION

- H.264
- UP TO 30fps
- G.711

INTELLIGENCE

- Analytics
- Motion Detection

OTHER

- DNA
- PoE
- Onvif

PHYSICAL



- Outdoor
- IR
- IK10
- Integral Mic

## Product Codes

Fisheye Camera	Camera
6MP Fisheye Camera with Built-In IR Illuminator	612740
12MP Fisheye Camera with Built-In IR Illuminator	614740

Product Code 66xxxx also available to order consisting of 61xxxx Product Code plus Enhanced Management Software License.

# Dimensions



# Specification

Camera Features	6MP	12MP
Sensor	1/1.8" Progressive CMOS	1/2.3" Progressive CMOS
Active Pixels (HxV)	6 MP (3072x2048)	12 MP (4000x3000)
Horizontal Resolution	> 800 TVL	> 1000 TVL
Minimum Sensitivity	Day: 0.01 lux (color). Night: 0.005 lux (mono). 30 IRE, F2.0, 1/30s shutter	Day: 0.01 lux (color). Night: 0.005 lux (mono). 30 IRE, F2.2, 1/30s shutter
Lens Options	1.55mm, Horizontal view angle 185°x185°, F2.0, Fixed Iris	1.57mm, Horizontal view angle 185°x185°, F2.2, Fixed Iris
Dynamic Range	WDR 100dB Max	
Gain Control	Auto/Manual setting	
Back Light Compensation	On/Off	
White Balance Mode	Auto/Manual	
Day/Night	True Day/Night with Mechanical IR Cut Filter	
IR Illuminator	Built-in IR Illuminator 850nm wavelength, effective distance >10m	
Video Resolution	4000x3000 pixels (12MP)*; 2880x2880 pixels (8MP)*; 2880x2160 pixels (6MP); 2048x1536 pixels (3MP); 704x576 pixels (D1); 704x480 pixels (D1) 352x288 pixels (SIF); 352x240 pixels (SIF)	
Signal/Noise Level	> 50dB	
Shutter	Rolling; Auto from 1/3 - 1/10,000 sec	
Exposure Control	Auto/Low Noise/Low Motion Blur/Manual	
Video Compression	Full frame rate, full color: H.264/MJPEG ; up to 30fps (ISO 14496-10)	
Privacy Zones	4 User Defined	
Video Bit Rate	User-configurable bit rates from 40Kbps up to 10Mbps	
Video Multi-Streaming	Up to 32Mbps total video output; Unlimited multicast connections. Up to four 8Mbps unicast connections	
Video Multi-Encoder	Edge Dewarping: Dual Streaming 3MP (2048 x 1536) @ 30fps + D1/SIF @ 30fps Native: Dual Streaming 12MP (4000x3000)* @ 15fps + D1/SIF @ 30fps or 3MP 2048x1536 pixels + or 6MP (3072 x 2048) @ 30fps + 720P @ 30fps	
Video Analytics	Motion Detection, Hooded, Tripwire, Intrusion	
Audio Compression	G.711	
Audio Bit Rate	32Kbps per channel	
Audio Resolution	Full Duplex, 8kHz or 16kHz sample rate. Mono Input, Mono Output	
Audio Analytics	Audio Detection	
Audio Input	Built-in microphone or Line in, RCA connector	
Audio Output	Line out, RCA connector	
Binary Input/Output	2 Pull up inputs for non powered contacts; 1 solid state opto-isolated relay output, Max 24V, 500mA	
Network Interface	IEEE802.3 and IETF standards: 10/100 Base-T Ethernet, IPv4/IPv6, TCP, UDP, RTP, RTSP, ICMP, IGMP, SNMP, HTTP, HTTPS, SSH, PPPoE, uPnP, QoS, DHCP	
Network Security	HTTPS / IP Filter / IEEE 802.1x	
Time	Embedded real-time clock, NTP client	
SD Storage	microSDHC 128GB support (card not included)**	
Dimension/Weight	150mm (dia) x 47.7mm (h) and 0.58Kg / 5.91in (dia) x 1.88in (h) and 1.28lb	
Regulatory	EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, EN 50130-4, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-11, IEC60068-2-27 (Shock), IEC60068-2-6 (Sine Vibration), UL60950-1	
Housing	White vandal resistant aluminium alloy including 500mm cable bundle	
Protection Rating	IP67, IK10 (IEC 62262)	
Electrical	Camera only: PoE (802.3af Class 0) or 12V DC @ 1.1A; 13W Power supply ordered separately (Product code: 110064; 130176)	
Operating Temperature	-30°C to 60°C (-22°F to 140°F)	
Cold Start	-30°C (-22°F)	
IndigoVision Software Requirements	Control Center v13.2 or later	
ONVIF	Profile S	

\* 12MP and 8MP resolution only available on 12MP variant. \*\*SDCard Storage independent of IndigoVision's NVRs.